

## AF-2 Medium Service Duct



### AF-2

Double ply bonded construction provides enhanced positive pressure performance and durability. Bi-directional construction for maximum flow efficiency. Manufactured with flame resistant UL94, V-0 approved

#### Applications

Particle Control  
Pellet and chip handling  
Areas of high vibration  
Large volume fume control materials.

#### Construction:

Material: Polyester fabric, Neoprene coated  
Construction: Two ply fabric over fully encapsulated spring steel wire.  
Diameters: 1.5" to 36".  
Weight: 6" I.D. = .9 lbs/ft.  
Length: 25 ft  
Compression Ratio: 2:1.  
Temperature Range: -40° to +250°F  
Color: Black

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	33	23	18	14	14	11	10	8
Negative Pressure Inch. H.g	28	27	25	18	14	8	5	3

Due to continuous improvements, technical data subject to change without notice

03.2105

Indianapolis, IN  
Haw River, NC  
Berlin, NJ  
Ajax, ON

Tel 317.334.1444 Fax 317.334.1535 800.526.6288  
Tel 336.578.2161 Fax 336.578.5554 800.334.4270  
Tel 856.768.2275 Fax 856.768.2385 800.225.0215  
Tel 905.686.5200 Fax 905.686.8349

THE  
**NOVAFLEX**  
GROUP

Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)