

## Vinyl Blower Duct



### Vinyl Blower Duct

An economical duct for large volume air transfer. This fabric reinforced vinyl coated blower duct is ideal for fresh air supply. Blower duct is manufactured without glues and adhesives, will not de-laminate. It is reinforced with a molecularly bonded wear strip for scuff resistance and a spring steel helix covered with a urethane wear strip for maximum abrasion resistance.

#### Applications

- Large Volume Air-conditioning
- Large Volume Heating
- Fresh air ventilation for utility manholes
- Fresh air supply for aviation cleaning
- Meets NFPA 701 and ULC S-109 large scale test requirements for flame retardancy

#### Special Features

- Standard plain ends
- Optional "attached soft cuffs"
- Optional buckles
- Scuff resistant
- Economical
- Compressible and flexible

#### Construction

- Material: Polyester single fabric coated with vinyl
- Construction: Single ply fabric over fully encapsulated spring steel helix with urethane wear strip
- Diameters: 6" to 24" I.D. Large sizes available
- O.D. : I.D. + 3/8"
- Bend Radius = 12" diam = 7"
- Pitch: 6"
- Weight: 6" I.D. = .7 lbs/ft
- Compression Ratio: 10:1
- Length: 25 ft
- Temperature Range: -20°F to +180°F
- Color: Yellow with black scuff guard
- Larger diameters and custom colors available upon request with a minimum order quantity.

12.2016

Berlin, NJ  
Indianapolis, IN  
Haw River, NC  
Ajax, ON

Tel 856.768.2275  
Tel 317.334.1444  
Tel 336.578.2161  
Tel 905.686.5200

Fax 856.768.2385  
Fax 317.334.1535  
Fax 336-578.5554  
Fax 905.686.8349

800.225.0215  
800.526.6288  
800.334.4270

THE  
**NOVAFLEX**  
GROUP



Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)