

U-Lok 100 General Service Duct



U-Lok 100

An extremely flexible duct with good low temperature and chemical resistance. Manufactured with UL 94 V-0 approved materials.

Applications

Dust Control
Air Handling
Light material handling
Fume control

Construction

Material: Polyester fabric, neoprene coated
Construction: mechanical bond, corrosion resistant helix
Diameters: 2" to 24"
Bend radius: 1.5 x I.D.
Weight: 6" I.D. = .9 lbs/ft
Standard length: 25ft
Compression ratio: 6:1
Temperature range: -45°F to +250°F

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	-	3.6	3.2	2.7	2.6	1.8	1.4	1.2
Negative Pressure. H.g.	-	2	1.8	1.3	1.2	1.1	0.73	0.6

08.2013

Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Haw River, NC Tel 336.578.2161 Fax 336-578.5554 800.334.4270
Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP 

Email: sales@novaflex.com
 Website: www.novaflex.com