

Novaflex

Welding Exhaust



U-Lok 700

Welding exhaust high temperature fume extraction ducting is designed specifically for improved indoor air quality. This single ply heavy duty duct provides high temperature service and extra durability.

Construction

Material	Tri-laminate-fiberglass, aluminized polyester/polyamid
Construction	Mechanical bond, corrosion resistant helix
Diameters	3" to 24"
Bend Radius	1.5" x I.D.
Lengths	25ft
Weight	6" I.D. = .8lbs/ft
Temperature range	-20°F to 300°F
Compression ratio	6:1
Color	Metallic silver

Due to continuous improvements, technical data subject to change without notice

Applications*

High temperature exhaust in hot environments
Welding fume control
Ideal for removal of welding fumes
Very flexible, ideal for difficult installs
Steel cut-off
Grinder exhaust

**Not recommended for contact with sparks or slag*

I.D.	Working Pressure/PSI	Negative Pressure Inch H.g
3"	4.3	3.2
4"	4	2.7
5"	3.6	2.4
6"	3.5	2.2
8"	3	1.8
10"	2.15	1.6
12"	1.8	1.25

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
GROUP

Email: sales@novaflex.com
Website: www.novaflex.com