

Novaflex®

Clear Extruded PVC Blower Duct

Clear Extruded PVC Blower Duct

All extruded PVC Blower duct provided an economical alternative to fabric reinforced blower duct. With a 0.045" gauge wall and spring steel wire, this product is as robust as they come. Rot and mildew resistant. Clear wall is unobtrusive. Excellent for inflatable amusements, tents etc.

Also available in regular thermoplastic rubber (TPR and Flame Retardant TPR) for higher temperature applications.

Applications: A/C Ventilation, Blower hose, Function tent HVAC, fans

Specifications

Material: Extruded PVC - Clear

Cover: Extruded molecularly bonded thermo plastic wearstrip

Diameters: 8" to 24"

Bend Radius = 12" diam = 7"

Weight: 24" I.D. = 3 lbs/ft

Compression Ratio: 10:1

Length: 25 ft

Temperature Range: -20°F to +165°F - PVC style

(-40°F to 275°F TPR-FR style)

Color: Clear with black scuff strip



Specification Chart

I.D.	8	10	12	14	16	18	20	22	24
Working Pressure/PSI	10	7	6.3	5	5	4	4	3	2
Negative Pressure Inch. H.g	5	5	4	3	3	1	1	1	1

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

12.2016

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk