

PVC Groundwork Hose



An economical alternative to cumbersome rubber hose

Clear PVC wall for visual monitoring.
An economical alternative to ALL urethane hose.

- UV stabilized for outdoor use
- Lightweight
- Good flexibility
- Smooth interior for optimum flow

Applications

- Wood chipping equipment
- Leaf collection equipment
- Medium duty material handling
- Plant debris collection

Specifications

Temperature: -20°F to +165°F
Standard length: 2.5" to 4" 100 ft, 6" 50ft
Bend radius: 4" I.D.= 5"
Weight per/ft: 4"=1.4lbs 6"=2.6lbs
Standard color: Translucent with black external wearstrip

Size inches	O.D.	Working Pressure (PSI)	Vacuum Rating Inch/Hg	Bend Radius	Standard Length (ft)	Approx. Wt lb/ft
2"	2.25"	40	Full	2.75"	100	0.85
2½"	3.28"	40	Full	2.75	100	1.0
3"	3.70"	40	Full	3"	100	1.2
4"	4.55"	35	Full	5"	100	1.4
6"	6.70"	30	28	11"	50	2.6

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

ver02.06

Berlin, NJ
Indianapolis, IN
Haw River, NC
Ajax, ON

Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP



Email: sales@novaflex.com
Website: www.novaflex.com