

HDAP & AGRI



Two Medium Duty Thermoplastic Hoses

Featuring a chemical resistant continuous inner tube with a molecularly bonded external wear strip for maximum durability

- Full wall tube for uniform chemical and temperature resistance
- Smooth interior for optimum product flow
- Full vacuum to 8" diameters
- Ideal for Medium Duty Material Handling
- Agricultural Fertilizers; Liquid Waste;
- Pool Maintenance and more

HDAP Industrial (black)

Available in lengths up to 100ft in diameters 1½" to 4", diameters 5" to 6", available in 60 ft lengths and 7" to 8" diameters available in 40 ft lengths.
Standard color: Black with black external helix
Temperature range: -65° to +225°F

AGRI (black with green helix)

Available in lengths of up to 100ft in diameters 1" to 4", in lengths up to 60 ft in 6" diameter.
Standard color: Black with green wear strip
Standard diameters: 1" to 6"
Temperature range: -60° to +225°F

AGRI (black with green helix)

I.D.	O.D.	MBR	Rec. WPSI @72°F	Approx Burst PSI @72°F	Vac Rating 72°F In./Hg	Wt per ft.
1"	1.36"	2.0"	50	220	29	0.30
1.25"	1.68"	3.0"	50	220	29	0.47
1.5"	1.88"	3.0"	50	190	29	0.50
2"	2.60"	4.5"	50	190	29	0.71
2.5"	2.98"	5.0"	50	180	29	0.82
3"	3.71"	7.5"	45	150	29	1.20
4"	4.70"	11.0"	40	140	29	1.40
6"	6.70"	21.0"	25	100	28	2.09

HDAP Industrial (black)

I.D.	MBR	Helix Pitch	Rec. WPSI @72°F	Vac Rating 72°F In./Hg	Wt per ft
1.5"	2"	.500"	40	29	0.70
2"	2"	.500"	40	29	0.97
2.5"	2"	.500"	35	29	1.20
3"	4"	.530"	35	29	1.40
4"	5"	.750"	30	29	1.70
5"	6"	.800"	30	28	1.80
6"	10"	.800"	30	28	1.90
8"	15"	.800"	30	27	2.90

Please Note: It is impossible to test Novaflex duct under all conditions to which it might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex duct under conditions that duplicate the service condition prior to installation. To confirm chemical suitability please consult your local sales office.

Berlin, NJ
Indianapolis, IN
Haw River, NC
Ajax, ON

Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP



Email: sales@novaflex.com
Website: www.novaflex.com