

Insulation Blowing



Novaflex Insulation Blowing Duct

A lightweight clear economical duct with outstanding flexibility. Ideal for:

Insulation Blowing

Cable Conduit

Fume Control

Light Duty Material Handling



CANADA: Tel: 905.686.5200 Fax 905.686.8349

USA: Tel: 856.768.2275 Fax: 856.768.2385

THE
NOVAFLEX
GROUP

Insulation Blowing Duct



Insulation Blowing Duct

A lightweight economical duct with outstanding flexibility; ideal for insulation blowing, cable conduit, fume control, light duty material handling.

An all extruded construction in ultra lightweight clear EVA for visual flow monitoring. This product offers both good puncture resistance and good chemical resistance.

Special Features

- Clear wall for product monitoring
- Lightweight for easy handling
- Good chemical resistance
- Abrasion resistant for light duty material handling

Applications

- Insulation blowing
- Fume control
- Lightweight material handling
- Cable conduit

Product Specifications

- Temperature range: -65°F to +200°F
- Standard length: 25 ft & 50 ft
- Standard diameters: 2" to 4"
- Standard colour: Clear with white external helix

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

ver05.09

Berlin, NJ
Indianapolis, IN
Haw River, NC
Ajax, ON

Tel 856.768.2275	Fax 856.768.2385	800.225.0215
Tel 317.334.1444	Fax 317.334.1535	800.526.6288
Tel 336.578.2161	Fax 336.578.5554	800.334.4270
Tel 905.686.5200	Fax 905.686.8349	

THE
NOVAFLEX[®]
GROUP 

Email: sales@novaflex.com
Website: www.novaflex.com