

Novaflex

Thermo Plastic PVCX



PVCX with Static Wire

"Easy to ground" Light weight PVC
Lightweight translucent PVC duct has an easily accessible static grounding wire. Economical dust and wood particle collection duct.

Novaflex PVC offers

Good resistance to oil, alkali and acids
Extremely flexible with good abrasion resistance
Clear construction for visual monitoring

Specifications

Temperature range: -20°F to +165°F

Lengths: 25 & 50 ft.

Sizes: 2" to 12" and in half inch sizes: 1½", 2½", 3½", 4½" and 5½".

Clear with rigid helix and static wire. FDA material.

Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W.P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	WGT (per foot)	Crush Tests ½ ID (lbs per foot)
2"	8.5"	3.0"	1.78	2.01	18	28	0.47	920
3"	9.5"	3.5"	1.62	1.77	14	28	0.53	740
4"	11.0"	4.5"	1.52	1.66	13.3	24	0.59	520
5"	13.5"	5.0"	1.22	1.34	12.6	19	0.75	410
6"	14.5"	5.5"	1.2	1.32	12	14	0.88	340
8"	19.0"	7.0"	0.74	0.81	10.7	5	1.3	300
10"	21.5"	8.5"	0.68	0.75	7	5	1.55	275
12"	24.0"	9.5"	0.65	0.72	6.3	4	1.75	200

The above data is provided as a general guide only. Friction loss through flexible ducting is dependent on the diameter, length, values, inner wall surface, general duct construction and number of bends. Friction loss values were obtained using 100ft straight runs with an air velocity of 3,500 FPM

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

Actual service temperature range is application dependent

Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
 Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
 Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
 Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
 GROUP 
 Email: sales@novaflex.com
 Website: www.novaflex.com