

Novaflex® Static Dissipating Urethane Duct



Novaflex® Static Dissipating Urethane Duct

- Manufactured from inherently dissipating urethane
- Safely reduces electrostatic build-up
- Excellent flow efficiency with reduced turbulence even in tight bends
- Excellent abrasion resistance and high tear strength
- Lightweight and extremely flexible

CANADA: Tel: 905.666.4970 Fax 905.666.9388
USA: Tel: 856.768.2275 Fax: 856.768.2385

THE
NOVAFLEX®
GROUP 

Static Dissipating Duct



Novaflex® TPU-SD (.030" wall gauge)

Static dissipating urethane reinforced with steel wire helix safely reduces static charges. TPU-SD is now manufactured using raw materials which meet the current requirements of the FDA for food contact applications when used in accordance with the requirements and limitations of 21 CFR: 175.105 and 177.2600a.

This specially-formulated, inherently static-dissipating grade of urethane, also maintains the TPU-SD duct's ability for permanent protection against electrostatic discharge.

- Excellent flexibility
- Maximum abrasion resistance
- Superior tear resistance and high tensile strength
- Clear construction for visual monitoring

Applications

Plastics processing, dust and shavings
Woodworking equipment
Plant debris collection
Dust collection
Material handling

Specifications

Wall gauge: 0.030"
Temperature range: -65°F to 200°F
Lengths: 25 & 50 ft
Sizes: 2" to 12"
Compression ratio: 2:1
Product Code: 9SFTPUW_ _SD

Larger diameters and metric sizes and heavier wall gauges available. Please contact factory.

Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W. P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	Wgt (per foot)	Crush Tests ½ ID (lbs per foot)
2"	9.5"	3.0"	1.72	1.84	22	29	0.44	780
3"	10.0"	3.5"	1.62	1.74	20	29	0.47	660
4"	11.5"	4.0"	1.29	1.42	18	26	0.56	510
5"	13.5"	5.0"	1.19	1.3	18	21	0.7	400
6"	14.5"	5.5"	1.17	1.28	16	16	0.84	350
8"	19.0"	7.0"	0.74	0.75	16	6	1.12	310
10"	21.0"	8.5"	0.71	0.73	14	5	1.24	270
12"	23.0"	9.5"	0.68	0.7	14	4.5	1.37	265

Static dissipating material with wire helix allows for safe grounding when used with metallic fittings. Conductivity of the duct should be tested regularly. Test the OHMS meter using conductive fittings inserted into each end of the duct. Point to point and point to ground testing performed on 4" duct resulted in readings between 1×10^8 and 1×10^{10} OHMS.

All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

ver03.11

Berlin, NJ
Indianapolis, IN
Haw River, NC
Whitby, ON

Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Tel 905.666.4970 Fax 905.666.9388

THE
NOVAFLEX
GROUP
Email: sales@novaflex.com
Website: www.novaflex.com

