

Novaflex

Thermoplastic Urethane Duct



Lavatory Waste Hose

Lavatory Waste Hose is a new crush and drag resistant thermoplastic polyurethane hose, reinforced with a crush resistant PVC helix that is resistant to traffic roll-overs and hauling over rough surfaces.

The smooth interior hose allows an unrestricted flow. With integral cuffs this hose provides an effective seal for all styles of lav fittings. It is made without glues, cements, or adhesives and is chemical, moisture and UV Ozone resistant.

Specifications

Temperature range: -65°F to +200°F

Lengths: Custom lengths available. Call for minimum quantities.

Sizes: 2" to 6"

Colour: Translucent blue with blue helix.

I.D	2	3	4	4½	5	6
Working Pressure /PSI	35	30	21	21	18	16
Negative Pressure Inch H.g	30	30	30	30	26	23

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

Berlin, NJ
Indianapolis, IN
Haw River, NC
Whitby, ON

Tel 856.768.2275
Tel 317.334.1444
Tel 336.578.2161
Tel 905.666.4970

Fax 856.768.2385
Fax 317.334.1535
Fax 336.578.5554
Fax 905.666.9388

800.225.0215
800.526.6288
800.334.4270

THE
NOVAFLEX
GROUP

Email: sales@novaflex.com

Website: www.novaflex.com