

## Medium Duty Duct Cleaning

### Crush resistant duct with excellent shape retention

Crush resistant duct without wire helix with excellent shape retention. Extremely flexible & compressible. Enhanced chemical resistance of TPR. Extremely smooth interior for superior flow. Heavy duty external wear strip protects against abrasion but will not scuff or mark surfaces. No wire.

#### Applications

Industrial & residential duct cleaning  
In plant dust control  
Shop vacuum systems  
Chemical fume control

#### Product Specifications

Material: 0.045" extruded thermo plastic rubber  
Temperature range: -60°F to 250°F  
Standard length: 25 ft & 50 ft up to 8", 10" - 25 ft.  
Weight: 1.8lbs - 8" diameter  
Standard diameters: 3 to 10"  
Compression Ratio: 2:1  
Standard colour: black with black external wear strip



Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W. P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	Wgt (per foot)
3"	9.0"	3.5"	1.6	1.72	7.5	24	0.7
4"	11.5"	4.5"	1.3	1.43	7.3	20	0.94
5"	13.5"	5.5"	1.23	1.34	7.2	16	1.0
6"	14.5"	6.5"	1.2	1.32	7	12	1.4
8"	19.0"	8.5"	0.7	0.77	6.7	5	1.85
10"	21.0"	10.0"	0.68	0.75	5.5	4.5	2.1

Berlin, NJ  
Indianapolis, IN  
Haw River, NC  
Whitby, ON

Tel 856.768.2275  
Tel 317.334.1444  
Tel 336.578.2161  
Tel 905.666.4970

Fax 856.768.2385  
Fax 317.334.1535  
Fax 336.578.5554  
Fax 905.666.9388

800.225.0215  
800.526.6288  
800.334.4270

THE  
**NOVAFLEX**  
GROUP



Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)