

## TPR Nova-Vac Hose

### Novaflex TPR Nova-Vac Vacuum Hose

Manufactured without solvents glues or adhesives SF-TPR provides outstanding performance and fatigue resistance. Smooth interior design allows for superior flow and maximum efficiency.

TPR Nova-Vac vacuum hose is the perfect hose for those applications that require excellent flexibility, full vacuum rating and light weight design. This hose is commonly used in the wood working industry for CNC/milling work, table vacuum systems and for those applications that require a flexible high vacuum hose for the transfer of wood dust.

#### Specifications:

Available in lengths of up to 100ft in diameters 1" to 4",  
in lengths up to 60 ft in 6" diameter.

Standard color: Black with black wearstrip

Standard diameters: 1" to 6"

Temperature range: -40° to +150°F



Product No	ID"	ID mm	OD"	OD mm	Vacuum	WP psi @70°F	MBR"	Wt/lbs per ft
9NFNOVA-VAC02	2	50 mm	2.6	66 mm	Full	50	4.5	0.71
9NFNOVA-VAC02.08	2.5	63 mm	2.98	76 mm	Full	50	5	0.82
9NFNOVA-VAC03	3	76 mm	3.71	94 mm	Full	45	7.5	1.20
9NFNOVA-VAC02.362	2.36	60 mm	2.84	72 mm	Full	50	4.8	0.79
9NFNOVA-VAC03.149	3.15	80 mm	3.86	98 mm	Full	43	8	1.10

*Please visit our web site to view our complete line of PVC and Urethane products that are suitable for highly abrasive woodworking applications*

<b>Indianapolis, IN</b>	Tel 317.334.1444	Fax 317.334.1535	800.526.6288
<b>Haw River, NC</b>	Tel 336.578.2161	Fax 336.578.5554	800.334.4270
<b>Berlin, NJ</b>	Tel 856.768.2275	Fax 856.768.2385	800.225.0215
<b>Whitby, ON</b>	Tel 905.666.4970	Fax 905.666.9388	

THE  
**NOVAFLEX**  
GROUP

Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)